

高炉开口钻具--钻杆

广泛应用于大型钢铁厂，特别是高炉输送液态钢。

(1) 材料/等级: DIN CK45, JIS S45C, SAE1045, AISI1045; DIN CK20, JIS S20C, SAE1020, AISI1020, ASTM A106B, ASTM A53B, ST45, ST42。

直径: hex.19mm-32mm, 直径 32mm-51mm

壁厚: 11mm-14mm (0.43-0.55)



长度: 1.0m-6m

我们根据全球客户的不同情况，定制设计，生产和服务。



高炉开口钎

图片	杆体长度		钻头尺寸		编码
	mm	in	mm	in	
	1830	6'	32	1 1/4"	ME32-18R32/H25
	2435	8'	32	1 1/4"	ME32-24R32/H25
	3050	10'	32	1 1/4"	ME32-30R32/H25
	3660	12'	32	1 1/4"	ME32-36R32/H25
	3830	12'6"	32	1 1/4"	ME32-38R32/H25
	4300	14'1"	32	1 1/4"	ME32-43R32/H25
	1830	6'	38	1 1/2"	ME38-18R38/R38 (ME38-18R38 / D30)
	2435	8'	38	1 1/2"	ME38-24R38/R38 (ME38-24R38 / D30)
	3050	10'	38	1 1/2"	ME38-30R38/R38 (ME38-30R38 / D30)
	3660	12'	38	1 1/2"	ME38-36R38/R38 (ME38-36R38 / D30)
	3830	12'6"	38	1 1/2"	ME38-38R38/R38 (ME38-38R38 / D30)
	4300	14'1"	38	1 1/2"	ME38-43R38/R38 (ME38-43R38 / D30)

单螺纹（双凸缘）螺纹钻杆

图片	杆体长度		钻头尺寸		编码
	mm	in	mm	in	
	1830	6'	32	1 1/4"	MT32-18 H25L
	2435	8'	32	1 1/4"	MT32-24 H25L
	3050	10'	32	1 1/4"	MT32-30 H25L
	3660	12'	32	1 1/4"	MT32-36 H25L
	3830	12'6"	32	1 1/4"	MT32-38 H25L
	4300	14'1"	32	1 1/4"	MT32-43 H25L
	1830	6'	38	1 1/2"	MT38-18 D30L
	2435	8'	38	1 1/2"	MT38-24 D30L
	3050	10'	38	1 1/2"	MT38-30 D30L
	3660	12'	38	1 1/2"	MT38-36 D30L
	3830	12'6"	38	1 1/2"	MT38-38D30L
	4300	14'1"	38	1 1/2"	MT38-43 D30L

单接头（双接头）焊接钻杆

图片	杆体长度		钻头尺寸		编码
	mm	in	mm	in	
	3500	11'6"	32	1 1/4"	MW32-35L
	4270	14'	32	1 1/4"	MW32-42L
	4420	14'6"	32	1 1/4"	MW32-44L
	5000	16'4"	32	1 1/4"	MW32-50L
	5400	17'7"	32	1 1/4"	MW32-54L
	6000	19'8"	32	1 1/4"	MW32-60L
	3500	11'6"	38	1 1/2"	MW38-35L
	4270	14'	38	1 1/2"	MW38-42L
	4420	14'6"	38	1 1/2"	MW38-44L
	5000	16'4"	38	1 1/2"	MW38-50L
	5400	17'7"	38	1 1/2"	MW38-54L
	6000	19'8"	38	1 1/2"	MW38-60L